2SC2736

Rev.F Apr.-2017

蓝箭电子 BLUE ROCKET ELECTRONICS

DATA SHEET

/ Descriptions

SOT-23 NPN Silicon NPN transistor in a SOT-23 Plastic Package.

/ Features


High f_T.

/ Applications


,

UHF/VHF frequency converter, local oscillator.

/ Equivalent Circuit



/ Pinning




PIN1 Base PIN 2 Emitter PIN 3 Collector


/ h_{FE} Classifications & Marking


h_{FE} Range	30 200
Marking	HTC

Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}	30	V


/ Electrical Characteristic Curve








/ Package Dimensions



/ Marking Instructions




H

TC

Note:

H	Company Code
TC	Product Type Code

( ) / Temperature Profile for IR Reflow Soldering(Pb-Free)



Note:

1	25 150	60 90sec;	1.Preheating:25~150 , Time:60~90sec.
2	245±5	5±0.5sec;	2.Peak Temp.:245±5 , Duration:5±0.5sec.
3	2 10 /sec.		3. Cooling Speed: 2~10 /sec.

/ Resistance to Soldering Heat Test Conditions

260±5	10±1 sec.	Temp.:260±5	Time:10±1 sec

/ Packaging SPEC.

/ REEL

	Units 包装数量	Dimension 包装尺寸 (unit: mm^3)