/ Descriptions

TO-263 ĮĮĮ Ł N ŏ MOS ß ŵ Ż ˥ N-CHANNEL MOSFET in a TO-263Plastic Package.

/ Features

Ĥ ŏ ɔ я ɾ ᵇ ɐ ɟ ɔ ķ ŋ Â ɥ ѧ ů ȏ


Low gate charge, Low Crss , Fast switching.

/ Applications

ɛ ŋ ʒ ƿ ɤ ŵ ' Â ɥ ɔ ◊ DF2GF ı ' ƹ Ω

It is very suitable for various AC/DC power conversion in switching mode operatio for system miniaturization and higher efficiency.

/ Equivalent Circuit



/ Pinning



PIN1 χ G PIN 2,4 χ D PIN 3 χ S


/ h_{FE} Classifications & Marking


ȸ м ˥ ب ˝ See Marking Instructions.


v ̈Ω Parameter	ϒ N Symbol	̈Ω Ö Rating	D Ɥ Unit
Drain-Source Voltage	V_{DSS}	500	V
Drain Current	I_D(Tc=25)	13	A
Drain Current	I_D(Tc=100)	8	A
Drain Current - Pulsed	I_{DM}	52	A
Gate-Source Voltage	V_{GSS}	±30	V
Single Pulsed Avalanche Energy	E_{AS}	860	mJ
Repetitive Avalanche Energy	E_{AR}	19.5	mJ
Avalanche Current	I_{AR}	13	A
Power Dissipation	P_D(Tc=25)	195	W
Operating and Storage Temperature Range	T_J,T_{STG}	-55 to 150	

v ̈Ω Parameter	ϒ N Symbol	Ⅱ ː ϯ ϒ Test Conditions	ω ṇ Ö Min	Ɛ ʒ Ö Typ	ω ᶻ Ö Max	D Ɥ Unit
Drain-Source Breakdown Voltage	BV_{DSS}	V_{GS}=0V I_D=250μA	500			V


/ Electrical Characteristic Curve








/ Package Dimensions



单位：mm


Dimensions In Millimeters		Dimensions In Millimeters	
Symbol	Min	Max	Min
A	4.30	4.70	
			9.00

/ Marking Instructions



ͻ ˝ χ	
BR χ	ѭ ҳ и Ґђ
46Q83 χ	ѭ ҙ ɴ Ґђ
---- χ	ѭ ɨ ғ ӈ ɴ Ґђ ɪ ҿ ɨ ғ ӈ ɴ Ψ ҏ
Note:	
BR:	Company Code
13N50:	Product Type.
****:	Lot No. Code, code change with Lot No.

( ) / Temperature Profile for IR Reflow Soldering(Pb-Free)



ب ˝ χ

1 Ĺ ♬ □ ỷ 25 Ḱ 150 ł ı ˋH ڑ 60 Ḱ 90sec;

2 Š Ө □ ỷ 245 ° 5 ł ı ˋH ڑ ˋY ﾊ ㎞ 5 ° 0.5sec;

3 ì ˙ ﾘ ˛ ɔ ﻉ ỷ ㎞ 2 Ḱ 10 ł /sec.

Note:

1.Preheating:25~150 ł , Time:60~90sec.

2.Peak Temp.:245 ° 5 ł , Duration:5 ° 0.5sec.

3. Cooling Speed: 2~10 ł /sec.

/ Resistance to Soldering Heat Test Conditions

□ ỷ χ 260 ° 5 ł ˋH ڑ χ 10 ° 1 sec. Temp.:260±5 Time:10±1 sec

/ Packaging SPEC.

ɔ ` ﾔ Ł / REEL

Package Type	Units			Dimension (unit mm³)
	Units/Reel /	Reels/Inner Box /	Units/Inner Box	