/ Descriptions

WR0585 ṂṂ Ḅ SQS ÆṀ ч s ǁ ᒣ Silicon PNP transistor in a TO-252 Plastic Package.

/ Features

Ҥ ѩ Ã Ԋ ı ق ɔ ė ă ´ ˎ ˚ Ḅ Ẕ ŧ ı ϟ ᵀ DHF0T434 ‰´ ב ׀ ، ớ ļ ∂ ı ṇ ғ β


Low Speed ,Load Formed for Surface Mount Application, Qualified to AEC-Q101 Standards for High Reliability, HF Product.

/ Applications


ṷ ŧ ѽ ᶻ ᴴ ı ◗ ′ ∩ ҁ Ẕ ŧ ϶ ∂

General Purpose Amplifier, Meet the stringent requirements of automotive applications.

/ Equivalent Circuit



/ Pinning



PIN1 χ Base PIN 2,4 χ Collector PIN 3 χ Emitter


/ h_{FE} Classifications & Marking


ð м ϒ ب ˝

See Marking Instructions.

v ″Ω Parameter	ϒ N Symbol	″Ω Ö Rating	D Ч Unit
Collector to Base Voltage	V_{CBO}	-100	V
Collector to Emitter Voltage	V_{CEO}	-100	V
Emitter to Base Voltage	V_{EBO}	-5.0	V


/ Electrical Characteristic Curve







/ Package Dimensions




单位：mm

Symbol	Min	Max
A	2.34	
B	0.95	1.25
e1	2.24	
b	0.70	
b1	0.45	0.55
c	0.45	0.55
c1	0.45	0.55
D	6.45	6.75
D1	5.10	5.50
K	0.60	

TO-252

/ Marking Instructions



ͻ ˝ χ	
BR χ	ᵻᵡ ϗ ᴺ Γъ
Q χ	ᵻᵡ ∩ ᶜ ṅ ᶠ ᵝ ‰ ᵡ
PᴹG65F χ	ᵻᵡ ᶠ ᵝ ȝ ᴺ
---- χ	ᵻᵡ ᶦ ᶠ ᵑ̌ ᴺ Γъ ᶦ ᵩ ᶦ ᶠ ᵑ̌ ᴺ Ψ ᖘ

Note:

BR:	Company Code
Q:	Automobile halogen-free product Code
MJD32C:	Product Type
****:	Lot No. Code, code change with Lot No

( ) / Temperature Profile for IR Reflow Soldering(Pb-Free)

ب ˝ χ

1 Ĺ ♬ □ ỷ 150 Ḱ 200 ɬ ı ̀H ڑ 60 Ḱ 120sec;

2 Š Ө □ ỷ 255 ° 5 ɬ ı ̀H ڑ ̀Y ʌ ʁ 5 ° 0.5sec;

3 ì ˙ ٢ ˛ ɔ ѕ ỷ ʁ 2 Ḱ 10 ɬ /sec.

Note:

1.Preheating:150~200 ɬ , Time:60~120sec.

2.Peak Temp.:255 ° 5 ɬ , Duration:5 ° 0.5sec.

3. Cooling Speed: 2~10 ɬ /sec.