/ Descriptions

1.5A ABF
1.5A Surface Mount Glass Passivated Bridge Rectifier, ABF thin package.

/ Features

1000V 1.5A
Glass Passivated Chip Junction,Reverse Voltage: 1000V,Forward Current:1.5A, Fast reverse recovery time,Designed for Surface Mount Application.Halogen free product.

/ Applications

.
General purpose.

/ Equivalent Circuit



/ Pinning



PIN	DESCRIPTION
1	Input Pin (~)
2	Input Pin (~)
3	Output Anode (+)
4	Output Cathode (-)



/ Marking

See Marking Instructions.

/ Absolute Maximum Ratings(Ta=25)

Parameter	Symbol	Rating	Unit
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	1000	V
Maximum RMS Voltage	V_{RMS}	700	V
Maximum DC Blocking Voltage	V_{DC}	1000	V
Average Rectified Output Current at T_c = 125	I_o	1.5	A
Peak Forward Surge Current 8.3 ms Single Half Sine Wave Superimposed on Rated Load	I_{FSM}	50	A
Typical Junction Capacitance Note1	C_j	35	pF
Typical Thermal Resistance Note2	R_{JA}	70	/W
Operating and Storage Temperature Range	T_j,T_{stg}	-55~150	

Note:

1.Measured at 1MHz and applied reverse voltage of 4 V D.C.

2. Mounted on glass epoxy PC board with 4 × 1.0" X 1.0" (2.54 X 2.54 cm) copper pad.

/ Electrical Characteristics(Ta=25)

Parameter	Symbol	Test Conditions	Rating	Unit
Forward Voltage per element	V_F	I_F=1.5A	1.3	V
Maximum DC Reverse Current at Maximum DC Blocking Voltage	I_R	T_a=25	5.0	A
		T_a=125	50	A
Maximum Reverse Recovery Time	t_{rr}	I_F =0.5A I_R=1.0A I_{rr}=0.25A	200	ns

/ Electrical Characteristic Curve



/ Package Dimensions



/ Marking Instructions

Marking

Type number	Marking code
FTB10F-15	F10F15



/ Marking Instructions



F10F15

******** 1 * 3 *

Note:

F10F15 Product Type Code

******** Lot No. Code The 1st * means:YM Code The last 3 * means:little Lot No Code

( ) / Temperature Profile for IR Reflow Soldering(Pb-Free)



						Note:	
1		25	150		60	90sec;	1.Preheating:25~150 , Time:60~90sec.
2		245±5				5±0.5sec;	2.Peak Temp.:245±5 , Duration:5±0.5sec.
3				2	10	/sec.	3. Cooling Speed: 2~10 /sec.

/ Resistance to Soldering Heat Test Conditions

260±5	10±1 sec.	Temp.:260±5	Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm^3)		
	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box 盒	Outer Box 箱
ABF	5000	2	10000	5	50000	13 ×15	336X336X40	380X335X366

/ Notices