MBR20H100CT

Rev.I Aug.-2021

DATA SHEET

MBR20H100CT

Rev.I Aug.-2021

DATA SHEET

/ Descriptions

TO-220

Schottky Barrier Diode in a TO-220 Plastic Package.

/ Features

Low power loss, high efficiency.

/ Applications

For use in low voltage,high frequency inverters, free wheeling, and polarity protection applications.

/ Equivalent Circuit

/ Pinning



Plj Anode Plj Cathode Plj Anode

/ h_{FE} Classifications & Marking

See Marking Instructions.

Parameter	Symbol	Rating	Unit

/ Electrical Characteristic Curve



VR(V)

VR(V)



/ Package Dimensions



/ Marking Instructions



BR

MBR20H100

CT:

****

Note:

BR:	Company Code
MBR20H100	Product Type.
CT:	Internal Structure
****:	Lot No. Code, code change with Lot No.

( ) / Temperature Profile for Dip Soldering(Pb-Free)



					Note:
1		25 150		60 90sec;	1.Preheating:25~150℃, Time:60~90sec.
2		255±5		5±0.5sec;	2.Peak Temp.:255±5℃, Duration:5±0.5sec.
3			2	10℃/sec.	3. Cooling Speed: 2~10℃/sec.

/ Resistance to Soldering Heat Test Conditions

270±5℃	10±1 sec.	Temp.:270±5℃	Time:10±1 sec

/ Packaging SPEC.

/ BULK

Package Type 封	Units					Dimension		(unit mm³)
	!"#$%&'(只%袋	&'($%)!!*+&,- 袋%盒	!"#$%)!!*+&,- 只%盒	)!!*+&,-*$%./#*+&,- 盒%箱	!"#$%./#*+&,- 只%箱	&'(	)!!*+&封-	./#*+&,-
0.1223%4	233							