/ Absolute Maximum Ratings(Ta=25)

v ̈Ω̣ Parameter	ɬ N Symbol	̈Ω̣ Ö Rating	D Ɉ Unit
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	40	V
Maximum RMS voltage	V_{RMS}	28	V
Maximum DC Blocking Voltage	V_{DC}	40	V
Maximum Average Forward Rectified Current Tc=100	$I_{F\ AV}$	0.2	A
Peak Forward Surge Current 8.3 ms Single Half Sine Wave Superimposed on Rated Load (JEDEC Method)	I_{FSM}	13	A
Operating and Storage Temperature Range	T_j,T_{stg}	-55~+125	

)

v ̈Ω̣ Parameter	ɬ N Symbol	⅃ ⁝ ̇ Ţ Test Conditions	ω̣ ṇ Ö Min	Ɛ ʒ Ö Typ	ω̣ ᶻ Ö Max	D Ɉ Unit
Maximum Instantaneous Forward Voltage	V_F	I_F=0.2A			0.6	V
Maximum DC Reverse Current at Rated DC Blocking Voltage	I_R	T_a=25			5	uA
		T_a=100			100	uA

/ Electrical Characteristic Curve







/ Package Dimensions



/ Marking Instructions



ب ˝ χ

K χ ⌘ ⅔ ᴵ Ɱ

VG χ ⌘ ⅔ ᴺ Ɱ

Note:

H: Company Code

SD: Product Type r -1.9086 TD( )Tj/TT9 1 ( )Tj0 -1.9029 T2640.1.960 04 Tc.2228